

CAPAROL TECHNICAL INFORMATION COMPACT Nr. 342

CapaMATT

INTERIOR MATT PAINT.

Field of Application	CAPAROL TRADE CapaMATT is a premium quality paint suitable for regular interior walls & ceilings. CapaMATT is high opacity and offers exceptional coverage and workability.
Pack Size	12.5l
Composition	Acrylic dispersion binder, titanium dioxide, calcium carbonate, silicates, water, additives and preservatives.
Colour Range	White / Tinted colours available
Optimum Coverage	Up to 15M ²
Application	Brush, Roller, Airless Spray Airless application a 517-519 tip at 2000 psi, medium to course filter
Drying Times	Under Normal Conditions recoatable 2-4 hours Completely dry in 3 days Lower temperatures will extend drying times Do not apply under +5°c
Storage	Keep paint cool but frost free
Thinner/cleaner	Water
Thinning	Regular application: add up to max. 1 part water to 20 parts paint Sealing new surfaces: add up to max. 1 part water with 10 parts paint Airless spray application: add up to max. 1 part water with 5 parts paint
Properties	VOC – free Emission minimized Solvent-free Low odour Water-thinnable Ecologically compatible Easy to apply Matt finish
Characteristics to DIN EN 13 300:	Wet abrasion class 3 (DIN 53 778) Opacity (hiding, covering power) class 2
Substrate Preparation	Make sure all surfaces are clean and free from loose or flaking coatings or other contaminants before application. Ensure new surfaces are fully dry. CapaMATT will adhere to most surfaces without a primer, but if unsure always try a test area before application. Clean or sand surfaces prior to application as necessary. Fill surface defects prior to application using a proprietary filler. See Caparol Trade Technical Information sheet 342 for full substrate pre-treatment schedule.
Unsuitable substrates	Do not apply direct to distemper paints, if unsure always try a test area before application. Heavily stained areas may require suitable primer before CapaMATT may be applied (Water stains, nicotine, soot).
System Information	Stir thoroughly before use. The recommended process to achieve premium finish is 2 coats of CapaMATT. However for pre-coated surfaces a single coat may be sufficient.

Health and Safety Information	<p>Ensure the area is well ventilated during application and drying.</p> <p>Avoid contact with eyes and skin.</p> <p>In case of contact with eyes, rinse immediately with clean cold water.</p> <p>If irritation persists consult your GP.</p> <p>Remove paint from skin using soap and water.</p> <p>When spraying, avoid breathing spray mist.</p> <p>Wearing of a suitable mask or respiratory device is advised during application.</p> <p>Minimum recommended respiratory protection: to BS EN 149:2001, FFP3</p> <p>Keep out of reach of children.</p>
Disposal	<p>Do not empty waste material into water courses or drains. In site conditions, do not empty onto the ground.</p> <p>Materials and all related packaging must be disposed of in a safe and preferably environmentally friendly manner.</p> <p>Dispose fully in accordance with local authority guidelines.</p>
EU limit value	Category (a/A): max 30g/l (2010). This product contains <1g/l of VOC
Advise (technical assistance)	If you require any more information please contact Caparol Technical helpline on the details below.
Customer service number	01785 811191 Fax 01785 818144
Email	tech@caparol.co.uk
Website	www.caparol.co.uk
Issued	January 2010

