

CAPAROL TECHNICAL INFORMATION COMPACT Nr. 331

CapaMAXX

Washable dead flat finish, high opacity with superb colour brilliance, low odour eco friendly paint.

Field of Application

Interior use for walls and ceilings, dead flat finish that will hide imperfect walls, designer paint finish that is easy to touch up and use, ideal for areas where paint odours are not desired on application.

Suitable Substrates

Plaster/plasterboard, brick, stone. (Interior only)

Vehicle & Composition

Synthetic dispersion to DIN 55 945 Polyvinyl acetate resin, Titanium dioxide, silicates, water, additives, preservative,

Preparation

All surfaces must be clean and dry, free from any material that could prevent good adhesion. All mould & mildew must be removed and treated before application (Caparol Capatox).

Interior

Plaster/Plasterboard, may be applied neat or thinned 5% tap water (no primer required) 2 coats for a standard finish.

Concrete, may be applied neat or thinned by 5% tap water (no primer required) 2 coats for standard finish.

Brick, may be applied neat or thinned by 5% tap water (no primer required) 2 coats for standard finish.

If you are unsure of adhesion then always do a test area first.

Properties Emission minimised and solvent free, water thinnable, low odour, plasticiser free, washable. .

Colour Range White / Over 5000 colours available (including RAL, BS, NCS).

Coverage 8-15m² per litre

Available sizes 5lt colour 5lt, 10lt white

Application Brush, Roller, Airless Spray
Airless application a 517-519 tip at 2000-2500 psi, medium to course filters.



Emission minimised solvent-free paint



Drying Times

Under normal conditions recoatable 2-4 hours washable after in 28 days.

Lower temperatures will extend drying times.

Do not apply under +5°C.

Storage Keep paint cool but frost free.

Thinning/Cleaning Tap Water.

Heavily stained areas may require suitable primer before CapaMAXX should be applied (Water stains, nicotine, soot).

System Information Stir thoroughly before use. The recommended process to achieve premium finish is 2 coats.

Health and Safety

Ensure the area is well ventilated during application and drying. Avoid contact with eyes and skin.

In case of contact with eyes, rinse immediately with clean cold water. If irritation persists consult your GP.

Remove paint from skin using soap and water. When spraying, avoid breathing spray mist. Wearing of a suitable mask or respiratory device is advised during application. Minimum recommended respiratory protection: to BS EN 149:2001, FFP3

Keep out of reach of children.

Disposal

Do not empty waste material into water courses or drains. In site conditions, do not empty onto the ground.

Materials and all related packaging must be disposed of in a safe and preferably environmentally friendly manner.

Dispose fully in accordance with local authority guidelines.

EU limit value Category (A/a: max 30g/l (2010) this product contains 1g/l of VOC

Advice (technical assistance)


If you require any more information please contact Caparol Technical helpline on the details below.

Customer service & colour cards or to find your nearest Distributor CALL: 01785 811191

Email: tech@caparol.co.uk

Website: www.caparol.co.uk

Issued: April 2011



Emission minimised solvent-free paint

